## IN THE CLAIMS

Please amend the claims as indicated below. A redlined version of the amended paragraphs is attached to this response as Appendix A.

Please replace the claims identified below with the following amended claims:

1. (Amended) A multi-carrier base station operating within a predetermined set of frequencies wherein data components of forward link data are transmitted simultaneously on a plurality of frequency bands, said base station comprising:

a first transmission subsystem for transmitting a sync channel message on a single carrier frequency of said predetermined set of frequencies; and

at least one additional transmission subsystem for transmitting remaining components of said forward link data on another carrier frequency of said predetermined set of frequencies.

8. (Amended) A multi-carrier mobile station comprising:

a control processor for controlling the operation of a plurality of receiver subsystems in accordance with frequency information indicated in a received sync channel message;

a first receiver subsystem for receiving said sync channel message on single carrier frequency and for providing said sync channel message to said control processor and for receiving a first portion of a multi-carrier signal;

at least one additional receiver subsystem for receiving additional portions of said multi-carrier signal.

9. (Amended) The mobile station of Claim 8 wherein said control processor decides whether to operate in a single carrier mode or a multi-carrier mode and directs said first receiver subsystem to tune to a frequency indicated in said sync channel message for the reception of a single band system when said mobile station decides to operate in a single carrier mode and directs said first receiver subsystem to tune to a first frequency and directs said at least one additional receiver subsystem to tune to at least one additional frequency when said mobile station decides to operate in a multi-carrier mode.

B2

Please add the following new claims 12 - 31:12. (New) A method of transmitting data components of forward link data in a communication system, comprising:

transmitting a sync channel message on a single carrier frequency within a predetermined set of frequencies; and

transmitting remaining components of said forward link data on another carrier frequency of said predetermined set of frequencies.

- 13. (New) The method of Claim 12 wherein said sync channel message indicates the center frequency of at least one multi carrier system in said predetermined set of frequencies.
- 14. (New) The method of Claim 12 wherein said sync channel message indicates the frequency of a single carrier system in said predetermined set of frequencies.
- 15. (New) The method of Claim 13 wherein said sync channel message indicates the frequency of a single carrier system in said predetermined set of frequencies.
- 16. (New) The method of Claim 13 wherein said sync channel message is transmitted on one of a set of a preferred frequency channels wherein the number of frequencies in said set of preferred frequency channels is less number of frequencies in said predetermined set of frequencies.
- 17. (New) The method of Claim 16 wherein said set of predetermined frequencies are the set of frequency bands in a personal communications system block of frequencies.
- 18. (New) The method of Claim 17 wherein the channel numbers of the set of preferred frequency channels are 75, 150 and 225.
- 19. (New) A method of receiving data components of forward link data in a communication system, comprising:

receiving a sync channel message and a first portion of a multi-carrier signal on a single carrier frequency; and

controlling operation of a plurality of receiver subsystems in accordance with frequency information indicated in said réceived sync channel message; and

receiving additional portions of said multi-carrier signal on another carrier frequency.

- 20. (New) The method/of Claim 19 further comprising deciding whether to operate in a single carrier mode or a multi-carrier mode and tuning to a frequency indicated in said sync changel message for the reception of a single band system when deciding to operate in a single carrier mode and tuning to at least one additional frequency when deciding fo operate in a multi-carrier mode.
- 21. (New) A multi-carrier base station operating within a predetermined set of frequencies wherein data components of forward link data are transmitted simultaneously on a plurality of frequency bands, said base station comprising:

means for transmitting a sync channel message on a single carrier frequency of said predetermined set of frequencies; and

means for transmitting remaining components of said forward link data on another carrier frequency of said predetermined set of frequencies.

- (New) The base station of Claim 21 wherein said sync channel message 22. indicates the center frequency of at least one multi carrier system in said predetermined set of frequencies.
- (New) The base station of Claim 21 wherein said sync channel message 23. indicates the frequency of a single carrier system in said predetermined set of frequencies.
- 24. (New) The base station of Claim 22 wherein said sync channel message indicates the frequency of a single carrier system in said predetermined set of frequencies.
- (New) The base station of Claim 22 wherein said sync channel message is transmitted on one of a set of a preferred frequency channels wherein the number of

frequencies in said set of preferred frequency channels is less number of frequencies in said predetermined set of frequencies.

- 26. (New) The base station of Claim 25 wherein said set of predetermined frequencies are the set of frequency bands in a personal communications system block of frequencies.
- 27. (New) The base station of Claim 26 wherein the channel numbers of the set of preferred frequency channels are 75, 150 and 225.
  - 28. (New) A multi-carrier mobile station comprising:

means for controlling the operation of a plurality of receiver subsystems in accordance with frequency information indicated in a received sync carrier message;

means for receiving said sync channel message on single carrier frequency and for providing said sync carrier message to said means for controlling and for receiving a first portion of a multi-carrier signal;

means for receiving additional portions of said multi-carrier signal.

- 29. (New) The mobile station of Claim 28 wherein said means for controlling decides whether to operate in a single carrier mode or a multi-carrier mode and directs said first receiver subsystem to tune to a frequency indicated in said sync channel message for the reception of a single band system when said mobile station decides to operate in a single carrier mode and directs said first receiver subsystem to tune to a first frequency and directs said at least one additional receiver subsystem to tune to at least one additional frequency when said mobile station decides to operate in a multi-carrier mode.
- 30. (New) The mobile station of Claim 28 wherein said means for controlling directs said first receiver subsystem to tune to one of a predetermined set of preferred frequencies.
- 31. (New) The mobile station of Claim 28 wherein said mobile station is operating within a personal communication system (PCS) set of frequencies and wherein said predetermined set of preferred frequencies consist of the frequency channel numbers 75, 150 and 225.

Carl B3